



with independent sideshift - 2 hydraulic functions - also available with round forks

Technical Data

Model	Cap. on forks kg	LCD mm	Cap. as clamp kg	LCD mm	S mm	A mm	B mm	D mm	E mm	G mm	ISO	V mm	CofG Z mm	Weight kg	Price €	Add-on price per 100mm fork length €
1T411	1.500	500	700	500	±100	340-1.300	750	40	100	1.200	2	133	268	236	On request	On request
1T411	1.500	500	700	500	±100	340-1.520	970	40	100	1.200	2	133	251	258	On request	On request
1T411	1.500	500	700	500	±100	350-1.700	1.130	40	100	1.200	2	133	244	269	On request	On request
1T411	1.500	500	700	500	±100	330-1.730	1.200	40	100	1.200	2	133	241	273	On request	On request
1,5T411	2.300	500	1.250	500	±100	320-1.500	970	45	120	1.200	2	133	266	323	On request	On request
1,5T411	2.300	500	1.250	500	±100	40-940	970	45	120	1.200	2	133	254	312	On request	On request
1,5T411	2.300	500	1.250	500	±100	330-1.680	1.130	45	120	1.200	2	133	253	335	On request	On request
1,5T411	2.300	500	1.250	500	±100	90-1.270	1.200	45	120	1.200	2	133	252	336	On request	On request
1,5T411	2.300	500	1.250	500	±100	310-1.710	1.200	45	120	1.200	2	133	270	339	On request	On request
1,5T401	2.300	500	1.250	500	-	260-1.260	850	45	120	1.200	2	126	260	300	On request	On request
2T411	2.800	500	2.000	500	±100	280-1.380	970	50	120	1.200	2	143	262	384	On request	On request
2T411	2.800	500	2.000	500	±100	320-1.620	1.130	50	120	1.200	2	143	257	396	On request	On request
2T411	2.800	500	2.000	500	±100	70-1.120	1.130	50	120	1.200	2	143	259	391	On request	On request
2T411	2.800	500	2.000	500	±100	120-1.420	1.330	50	120	1.200	2	143	252	408	On request	On request
2T411	2.800	500	2.000	500	±100	320-1.820	1.330	50	120	1.200	2	143	250	412	On request	On request
2T411	2.800	500	2.000	500	±100	280-1.380	970	50	120	1.200	3	143	262	384	On request	On request
2T411	2.800	500	2.000	500	±100	320-1.620	1.130	50	120	1.200	3	143	257	396	On request	On request
2T411	2.800	500	2.000	500	±100	70-1.120	1.130	50	120	1.200	3	143	259	391	On request	On request
2T411	2.800	500	2.000	500	±100	120-1.420	1.330	50	120	1.200	3	143	252	408	On request	On request
2T411	2.800	500	2.000	500	±100	320-1.820	1.330	50	120	1.200	3	143	250	412	On request	On request
2T401	2.800	500	2.000	500	-	300-1.300	850	50	120	1.200	2	136	282	339	On request	On request
2T401	2.800	500	2.000	500	-	300-1.300	850	50	120	1.200	3	136	282	339	On request	On request
3T411	3.600	500	2.500	500	±100	260-1.560	1.130	50	150	1.200	3	152	255	510	On request	On request
3T411	3.600	500	2.500	500	±100	260-1.760	1.330	50	150	1.200	3	152	249	529	On request	On request
3T411	3.600	500	2.500	500	±100	130-1.630	1.460	50	150	1.200	3	152	245	539	On request	On request
3T411	3.600	500	2.500	500	±100	260-1.890	1.460	50	150	1.200	3	152	245	541	On request	On request

Model	Cap. on forks kg	LCD mm	Cap. as clamp kg	LCD mm	S mm	A mm	B mm	D mm	E mm	G mm	ISO	V mm	CofG Z mm	Weight kg	Price €	Add-on price per 100mm fork length €
4T411	4.150	500	2.900	500	±100	260-1.560	1.130	50	150	1.200	3	162	245	572	On request	On request
4T411	4.150	500	2.900	500	±100	260-1.760	1.330	50	150	1.200	3	162	240	591	On request	On request
4T411	4.150	500	2.900	500	±100	130-1.630	1.460	50	150	1.200	3	162	237	603	On request	On request
4T411	4.150	500	2.900	500	±100	260-1.890	1.460	50	150	1.200	3	162	236	606	On request	On request
4,5T411	5.000	500	3.500	500	±100	230-1.480	1.200	60	150	1.200	3	188	253	689	On request	On request
4,5T411	5.000	500	3.500	500	±100	250-1.650	1.330	60	150	1.200	3	188	248	709	On request	On request
4,5T411	5.000	500	3.500	500	±100	120-1.520	1.460	60	150	1.200	3	188	245	725	On request	On request
4,5T411	5.000	500	3.500	500	±100	220-1.720	1.460	60	150	1.200	3	188	244	728	On request	On request
4,5T411	5.000	500	3.500	500	±100	260-1.890	1.550	60	150	1.200	3	188	241	744	On request	On request
4,5T411.1	5.000	500	3.500	500	±100	230-1.480	1.200	60	150	1.200	3	178	250	687	On request	On request
4,5T411.1	5.000	500	3.500	500	±100	250-1.650	1.330	60	150	1.200	3	178	246	705	On request	On request
4,5T411.1	5.000	500	3.500	500	±100	120-1.520	1.460	60	150	1.200	3	178	243	718	On request	On request
4,5T411.1	5.000	500	3.500	500	±100	260-1.890	1.550	60	150	1.200	3	178	240	734	On request	On request
4,8T411	5.000	600	3.200	600	±100	230-1.480	1.200	70	150	1.200	3	178	274	733	On request	On request
4,8T411	5.000	600	3.200	600	±100	250-1.650	1.330	70	150	1.200	3	178	270	752	On request	On request
4,8T411	5.000	600	3.200	600	±100	120-1.520	1.460	70	150	1.200	3	178	267	765	On request	On request
4,8T411	5.000	600	3.200	600	±100	260-1.890	1.550	70	150	1.200	3	178	263	781	On request	On request
5T411	6.200	600	3.500	600	±160	240-1.740	1.460	70	150	1.200	4	176	244	855	On request	On request
5T411	6.200	600	3.500	600	±160	280-1.910	1.550	70	150	1.200	4	176	242	868	On request	On request
5T411	6.200	600	3.500	600	±160	550-2.450 ¹⁾	1.550	70	150	1.200	4	176	234	933	On request	On request
5T411	6.200	600	3.500	600	±160	280-2.180	1.820	70	150	1.200	4	176	236	905	On request	On request
6T411B	8.000	600	4.800	600	±160	180-1.810	1.550	60	200	1.200	4	219	238	1.410	On request	On request
6T411B	8.000	600	4.800	600	±160	140-2.040	1.860	60	200	1.200	4	219	229	1.499	On request	On request
6T411B	8.000	600	4.800	600	±160	340-2.440	1.860	60	200	1.200	4	219	229	1.506	On request	On request
8T411B	8.000	900	6.500	600	VSS	310-2.510	2.200	70	200	1.200	4	309	241	2.045	On request	On request

The Fork Clamp can be used for the transportation of palletised goods as well as for clamping purposes.

Slip-on arms in different versions easily turn the Fork Clamp into a special clamp.

1) Transport of europallets lengthwise not possible.

Also available without sideshift, model T401

Fork Positioner with cylinder- and sideshift protection upon request.

Load Backrest see model T179.

With screw-on forks available upon request T411A



Specification:

The variously applicable Fork Clamp T411 is the base for all clamps of KAUP. Therefore, this attachment particularly suitable for hard use can be adapted very well to the individual demands. No matter, whether different hook-on fork cross sections for divergent charges, changed hook-on fork forms or the combination with other attachments: KAUP makes it possible.

Qualities:

- For hard onsets suitable
- Good visibility conditions
- Good residual capacity
- Independent sideshift serially
- Screw-on forks and round prongs optionally
- Load backrest optionally
- Optionally the most different puttable on clamp arms